

Introduction to Presentation Attack Detection in Fingerprint Biometrics

Javier Galbally, Julian Fierrez, Raffaele Cappelli, and Gian Luca Marcialis

```
(filename: chapter01/main.tex)
(corresponding author: Julian Fierrez (BiDA Lab, Universidad
Autonoma de Madrid, SPAIN))
(authors: Javier Galbally (European Commission, Joint Research
Centre, Ispra, Italy), Raffaele Capelli (Universit di Bologna,
Cesena, Italy), Gian Luca Marcialis (Universit di Cagliari,
Italy))
(status: EMPTY [NO])
(status: DRAFT [YES])
(status: COMPLETED [NO])
(action required: to write)
```

Abstract This chapter provides an introduction to Presentation Attack Detection (PAD) in fingerprint biometrics, also coined anti-spoofing, describes early developments in this field, and briefly summarizes recent trends and open issues.

Javier Galbally
European Commission, Joint Research Centre, Ispra, Italy, e-mail: javier.galbally@ec.europa.eu

Julian Fierrez
Biometrics and Data Pattern Analytics - BiDA Lab, Universidad Autonoma de Madrid, Madrid, Spain, e-mail: julian.fierrez@uam.es

Raffaele Capelli
Universit di Bologna, Cesena, Italy, e-mail: raffaele.cappelli@unibo.it

Gian Luca Marcialis
Universit di Cagliari, Italy, e-mail: marcialis@unica.it

1 Introduction

“*Fingerprints cannot lie, but liars can make fingerprints*”. Unfortunately, this paraphrase of an old quote attributed to Mark Twain¹ has been proven right in many occasions now.

As the deployment of fingerprint systems keeps growing year after year in such different environments as airports, laptops or mobile phones, people are also becoming more familiar to their use in everyday life and, as a result, the security weaknesses of fingerprint sensors are becoming better known to the general public. Nowadays it is not difficult to find websites or even tutorial videos, which give detail guidance on how to create fake fingerprints which may be used for spoofing biometric systems.

As a consequence, the fingerprint stands out as one of the biometric traits which has arisen the most attention not only from researchers and vendors, but also from the media and users, regarding its vulnerabilities to Presentation Attacks (PAs) (aka spoofing). This increasing interest of the biometric community in the security evaluation of fingerprint recognition systems against presentation attacks has led to the creation of numerous and very diverse initiatives in this field: the publication of many research works disclosing and evaluating different fingerprint presentation attack approaches [83, 66, 99, 92]; the proposal of new Presentation Attack Detection (PAD) (aka anti-spoofing) methods [33, 6, 36]; related book chapters [35, 55]; PhD and MSc Thesis which propose and analyse different fingerprint PA and PAD techniques [28, 87, 51, 12]; several patented fingerprint PAD mechanisms both for touch-based and contactless systems [52, 90, 47, 34, 50]; the publication of Supporting Documents and Protection Profiles in the framework of the security evaluation standard Common Criteria for the objective assessment of fingerprint-based commercial systems [18, 13]; the organization of competitions focused on vulnerability assessment to fingerprint presentation attacks [40, 17, 79]; the acquisition of specific datasets for the evaluation of fingerprint protection methods against direct attacks [38, 2, 94], the creation of groups and laboratories which have the evaluation of fingerprint security as one of their major tasks [11, 77, 19]; or the acceptance of several European Projects on fingerprint PAD as one of their main research interests [10, 96].

The aforementioned initiatives and other analogue studies, have shown the importance given by all parties involved in the development of fingerprint-based biometrics to the improvement of the systems security and the necessity to propose and develop specific protection methods against PAs in order to bring this rapidly emerging technology into practical use. This way, researchers have focused on the design of specific countermeasures that enable fingerprint recognition systems to detect fake samples and reject them, improving this way the robustness of the applications.

In the fingerprint field, besides other PAD approaches such as the use of multi-biometrics or challenge-response methods, special attention has been paid by re-

¹ Figures do not lie, but liars do figure.

searchers and industry to the so-called *liveness detection* techniques. These algorithms use different physiological properties to distinguish between real and fake traits. Liveness assessment methods represent a challenging engineering problem as they have to satisfy certain demanding requirements [56]: (i) non-invasive, the technique should in no case be harmful for the individual or require an excessive contact with the user; (ii) user friendly, people should not be reluctant to use it; (iii) fast, results have to be produced in a very reduced interval as the user cannot be asked to interact with the sensor for a long period of time; (iv) low cost, a wide use cannot be expected if the cost is excessively high; (v) performance, in addition to having a good fake detection rate, the protection scheme should not degrade the recognition performance (i.e., false rejection) of the biometric system.

Liveness detection methods are usually classified into one of two groups: (i) *Hardware-based* techniques, which add some specific device to the sensor in order to detect particular properties of a living trait (e.g., fingerprint sweat, blood pressure, or odor); (ii) *Software-based* techniques, in this case the fake trait is detected once the sample has been acquired with a standard sensor (i.e., features used to distinguish between real and fake traits are extracted from the biometric sample, and not from the trait itself).

The two types of methods present certain advantages and drawbacks over the other and, in general, a combination of both would be the most desirable protection approach to increase the security of biometric systems. As a coarse comparison, hardware-based schemes usually present a higher fake detection rate, while software-based techniques are in general less expensive (as no extra device is needed), and less intrusive since their implementation is transparent to the user. Furthermore, as they operate directly on the acquired sample (and not on the biometric trait itself), software-based techniques may be embedded in the feature extractor module which makes them potentially capable of detecting other types of illegal break-in attempts not necessarily classified as presentation attacks. For instance, software-based methods can protect the system against the injection of reconstructed or synthetic samples into the communication channel between the sensor and the feature extractor [15, 14].

Although, as shown above, a great amount of work has been done in the field of fingerprint PAD and big advances have been reached over the last two decades, the attacking methodologies have also evolved and become more and more sophisticated. This way, while many commercial fingerprint readers claim to have some degree of PAD embedded, many of them are still vulnerable to presentation attack attempts using different artificial fingerprint samples. Therefore, there are still big challenges to be faced in the detection of fingerprint direct attacks.²

This chapter represents an introduction to the problem of fingerprint PAD [39, 41]. More comprehensive and up to date surveys of recent advances can be found elsewhere [59, 93, 49, 91]. The rest of the chapter is structured as follows. An overview into early works in the field of fingerprint PAD is given in Section 2, while Section 3 provides a summary of recent trends and main open issues. A brief de-

² <https://www.iarpa.gov/index.php/research-programs/odin/>

scription of large and publicly available fingerprint spoofing databases is presented in Section 4. Conclusions are finally drawn in Sect. 5.

2 Early Works in Fingerprint Presentation Attack Detection

The history of fingerprint forgery in the forensic field is probably almost as old as that of fingerprint development and classification itself. In fact, the question of whether or not fingerprints could be forged was positively answered [105] several years before it was officially posed in a research publication [104].

Regarding modern automatic fingerprint recognition systems, although other types of attacks with dead [89] or altered [112] fingers have been reported, almost all the available vulnerability studies regarding presentations attacks are carried out either by taking advantage of the residual fingerprint left behind on the sensor surface, or by using some type of gummy fingertip (or even complete prosthetic fingers) manufactured with different materials (e.g., silicone, gelatin, plastic, clay, dental molding material or glycerin). In general, these fake fingerprints may be generated with the cooperation of the user, from a latent fingerprint or even from a fingerprint image reconstructed from the original minutiae template [107, 83, 66, 99, 95, 106, 37, 8, 38].

These very valuable works and other analogue studies, have highlighted the necessity to develop efficient protection methods against presentation attacks. One of the first efforts in fingerprint PAD initiated a research line based on the analysis of the skin perspiration pattern which is very difficult to be faked in an artificial finger [33, 81]. These pioneer studies, which considered the periodicity of sweat and the sweat diffusion pattern, were later extended and improved in two successive works applying a wavelet-based algorithm and adding intensity-based perspiration features [88, 97]. These techniques were finally consolidated and strictly validated on a large database of real, fake and dead fingerprints acquired under different conditions in [2]. Recently, a novel region-based liveness detection approach also based on perspiration parameters and another technique analyzing the valley noise have been proposed by the same group [98, 32]. Part of these approaches have been implemented in commercial products [71], and have also been combined with other morphological features [1, 60] in order to improve the presentation attack detection rates [61].

A second group of fingerprint liveness detection techniques has appeared as an application of the different fingerprint distortion models described in the literature [16, 9, 21]. These models have led to the development of a number of liveness detection techniques based on the flexibility properties of the skin [22, 6, 113, 111]. In most of these works the user is required to move his finger while pressing it against the scanner surface, thus deliberately exaggerating the skin distortion. When a real finger moves on a scanner surface, it produces a significant amount of distortion, which can be observed to be quite different from that produced by fake fingers which are usually more rigid than skin. Even if highly elastic materials are used, it seems

very difficult to precisely emulate the specific way a real finger is distorted, because the behavior is related to the way the external skin is anchored to the underlying derma and influenced by the position and shape of the finger bone.

Other liveness detection approaches for fake fingerprint detection include: the combination of both perspiration and elasticity related features in fingerprint image sequences [44]; fingerprint-specific quality-related features [100, 36]; the combination of the local ridge frequency with other multiresolution texture parameters [1]; techniques which, following the perspiration-related trend, analyze the skin sweat pores visible in high definition images [64, 67]; the use of electric properties of the skin [65]; using several image processing tools for the analysis of the finger tip surface texture such as wavelets [69], or three very related works using gabor filters [73], ridgelets [74] and curvelets [72]; analyzing different characteristics of the Fourier spectrum of real and fake fingerprint images [29, 45, 46, 54, 62].

A critical review of some of these solutions for fingerprint liveness detection was presented in [30]. In a subsequent work [31], the same authors gave a comparative analysis of the PAD methods efficiency. In this last work we can find an estimation of some of the best performing static (i.e., measured on one image) and dynamic (i.e., measured on a sequence of images) features for liveness detection, that were later used together with some fake-finger specific features in [62] with very good results. Different static features are also combined in [25], significantly improving the results of the individual parameters. Other comparative results of different fingerprint PAD techniques are available in the results of the 2009 and 2011 Fingerprint Liveness Detection Competitions (LivDet 2009 and LivDet 2011) [63, 109].

In addition, some very interesting hardware-based solutions have been proposed in the literature applying: multispectral imaging [76, 86], an electrotactile sensor [110], pulse oximetry [85], detection of the blood flow [52], odor detection using a chemical sensor [7], or a currently very active research trend based on Near Infrared (NIR) illumination and Optical Coherence Tomography (OCT) [23, 57, 24, 53, 20, 70].

More recently, a third type of protection methods which fall out of the traditional two-type classification software- and hardware-based approaches have been started to be analyzed in the field of fingerprint PAD. These protection techniques focus on the study of biometric systems under direct attacks at the *score level*, in order to propose and build more robust matchers and fusion strategies that increase the resistance of the systems against presentation attack attempts [84, 58, 42, 4, 5].

Outside the research community, some companies have also proposed different methods for fingerprint liveness detection such as the ones based on ultrasounds [101, 78], light measurements [82], or a patented combination of different unimodal experts [102]. A comparative study of the PAD capabilities of different commercial fingerprint sensors may be found in [48].

Although the vast majority of the efforts dedicated by the biometric community in the field of fingerprint presentation attacks and PAD are focused on touch-based systems, some works have also been conducted to study the vulnerabilities of contactless fingerprint systems against direct attacks and some protection methods to enhance their security level have been proposed [81, 34, 103].

The approaches mentioned above represent the main historical developments in fingerprint PAD until ca. 2012/2013. For a survey of more recent and advanced methods in the last 10 years we refer the reader to [59, 93, 49, 91], and the ODIN program.³

3 A brief view on where we are

In the next chapters of the book, the reader will be able to find information about the most recent advances in fingerprint presentation attack detection. This section merely summarizes some ongoing trends in the development of PADs and some of the main open issues.

As stated in the previous Section, independent and general-purpose descriptors were proposed for feature extraction since from 2013 [93]. In general, these feature looked for minute details of the fake image which are added or deleted, impossible to catch by the human eye. This was typically done by appropriate banks of filters aimed at derive a set of possible patterns. The related feature sets can be adopted to distinguish live from fake fingerprint by machine learning methods.

“Textural features” above looked as the most promising until the advent of deep learning approaches [49, 91]. These, thanks to the increased availability of data sets, allowed the design of a novel generation of fingerprint PAD [94, 26, 80] which exploited the concept of “patch”, a very small portion of the fingerprint image to be processed instead of taking the image as a whole input to the network. However, textural features have not yet left behind because of their expressive power and the fact that they explicitly rely on the patch definition [108, 3].

Among the main challenges to be faced with in the near future, it is important to mention [43]:

- assessing the robustness of anti-spoofing methods against novel presentation attacks in terms of fabrication strategy, adopted materials, sensor technology; for instance, in [27] it has been shown that the PAD error rates of software-based approaches can show a three-fold increase when tested on PA materials not seen during training;
- designing effective methods to embed PAD in fingerprint verification systems [68], including the need for computationally efficient PAD techniques, to be used on low-resources systems such as embedded devices and low-cost smartphones;
- improving explainability of PAD systems; the use of CNNs is providing great benefits to fingerprint PAD performance, but such solutions are usually considered as “black boxes” shedding little light on how and why they actually work. It is important to gain insights into the features that CNNs learn, so that system designers and maintainers can understand why a decision is made and tune the system parameters if needed.

³ <https://www.iarpa.gov/index.php/research-programs/odin/>

4 Fingerprint Spoofing Databases

The availability of public datasets comprising real and fake fingerprint samples and of associated common evaluation protocols is basic for the development and improvement of fingerprint PAD methods.

However, in spite of the large amount of works addressing the challenging problem of fingerprint protection against direct attacks (as shown in Section 2), in the great majority of them, experiments are carried out on proprietary databases which are not distributed to the research community.

Currently, the two largest fingerprint spoofing databases publicly available for researchers to test their PAD algorithms are:

- LivDet DBs (LivDet 2009-2021 DBs) [40, 17, 79]: These data sets, which share the acquisition protocols and part of the samples, are available from 2009 to 2021 Fingerprint Liveness Detection Competitions websites⁴⁵ and are divided into the same train and test set used in the official evaluations. Over seven editions, LivDet shared with the research community over 20,000 fake fingerprint images made up of a large set of materials (play doh, silicone, gelatine, latex...) on a wide brands of optical and solid-state sensors. Over years, LivDet competitions also proposed challenges as the evaluation of embedding fingerprint PAD and matching [17, 79], and of a novel approach to provide spoofs called “Screen-spoof” directly from the user’s smartphone screen [17]. The LivDet datasets are available for researchers by signing the license agreement.
- ATVS-Fake Fingerprint DB (ATVS-FFp DB) [38]: This database is available from the Biometrics group at UAM⁶. It contains over 3,000 real and fake fingerprint samples coming from 68 different fingers acquired using a flat optical sensor, a flat capacitive sensor and a thermal sweeping sensor. The gummy fingers were generated with and without the cooperation of the user (i.e., recovered from a latent fingerprint) using modeling silicone.

5 Conclusions

The study of the vulnerabilities of biometric systems against presentation attacks has been a very active field of research in recent years [75]. This interest has led to big advances in the field of security-enhancing technologies for fingerprint-based applications. However, in spite of this noticeable improvement, the development of efficient protection methods against known threats (usually based on some type of self-manufactured gummy finger) has proven to be a challenging task.

Simple visual inspection of an image of a real fingerprint and its corresponding fake sample shows that the two images can be very similar and even the human eye

⁴ <http://livdet.diee.unica.it>

⁵ <http://people.clarkson.edu/projects/biosal/fingerprint/index.php>

⁶ <http://biometrics.eps.uam.es/>

may find it difficult to make a distinction between them after a short inspection. Yet, some disparities between the real and fake images may become evident once the images are translated into a proper feature space. These differences come from the fact that fingerprints, as 3-D objects, have their own optical qualities (absorption, reflection, scattering, refraction), which other materials (silicone, gelatin, glycerin) or synthetically produced samples do not possess. Furthermore, fingerprint acquisition devices are designed to provide good quality samples when they interact, in a normal operation environment, with a real 3-D trait. If this scenario is changed, or if the trait presented to the scanner is an unexpected fake artifact, the characteristics of the captured image may significantly vary.

In this context, it is reasonable to assume that the image quality properties of real accesses and fraudulent attacks will be different and therefore image-based presentation attack detection in fingerprint biometrics would be feasible. Key early works in this regard have been summarized in the present chapter.

Overall, the chapter provided a general overview of the progress which was initially made in the field of fingerprint PAD and a brief summary about current achievements, trends, and open issues, which will be further developed in the next chapters.

Acknowledgements This work was mostly done (2nd Edition of the book) in the context of the TABULA RASA and BEAT projects funded under the 7th Framework Programme of EU. The 3rd Edition update has been made in the context of EU H2020 projects PRIMA and TRESPASS-ETN. This work was also partially supported by the Spanish project BIBECA (RTI2018-101248-B-I00 MINECO/FEDER).

Index

7th European Framework Programme (FP7), 8
Anti-Spoofing (term to be deprecated), 2
Fingerprint, 2
Presentation Attack (PA), 2
Presentation Attack Detection (PAD), 2
Spoofing (term to be deprecated), 2

References

1. Abhyankar, A., Schuckers, S.: Fingerprint liveness detection using local ridge frequencies and multiresolution texture analysis techniques. In: Proc. IEEE Int. Conf. on Image Processing (ICIP) (2006)
2. Abhyankar, A., Schuckers, S.: Integrating a wavelet based perspiration liveness check with fingerprint recognition. *Pattern Recognition* **42**, 452–464 (2009)
3. Agarwal, S., Rattani, A., Chowdary, C.R.: A comparative study on handcrafted features v/s deep features for open-set fingerprint liveness detection. *Pattern Recognition Letters* **147**, 34–40 (2021). DOI 10.1016/j.patrec.2021.03.032
4. Akhtar, Z., Fumera, G., Marcialis, G.L., Roli, F.: Robustness analysis of likelihood ratio score fusion rule for multi-modal biometric systems under spoof attacks. In: Proc. IEEE Int. Carnahan Conf. on Security Technology (ICSST), pp. 237–244 (2011)
5. Akhtar, Z., Fumera, G., Marcialis, G.L., Roli, F.: Evaluation of serial and parallel multibiometric systems under spoofing attacks. In: Proc. Int. Conf. on Biometrics: Theory, Applications and Systems (BTAS) (2012)
6. Antonelli, A., Capelli, R., Maio, D., Maltoni, D.: Fake finger detection by skin distortion analysis. *IEEE Trans. on Information Forensics and Security* **1**, 360–373 (2006)
7. Baldiserra, D., Franco, A., Maio, D., Maltoni, D.: Fake fingerprint detection by odor analysis. In: Proc. IAPR Int. Conf. on Biometrics (ICB), pp. 265–272. Springer LNCS-3832 (2006)
8. Barral, C., Tria, A.: Fake fingers in fingerprint recognition: Glycerin supersedes gelatin. In: Formal to Practical Security, LNCS 5458, pp. 57–69 (2009)
9. Bazen, A.M., Gerez, S.H.: Fingerprint matching by thin-plate spline modelling of elastic deformations. *Pattern Recognition* **36**, 1859–1867 (2003)
10. BEAT: BEAT: Biometrics Evaluation and Testing (2012). <http://www.beat-eu.org/>
11. Biometrics Institute: Biometric Vulnerability Assessment Expert Group (2011). <http://www.biometricsinstitute.org/pages/biometric-vulnerability-assessment-expert-group-bvaeg.html>
12. Blomme, J.: Evaluation of biometric security systems against artificial fingers. Master's thesis, Linköping University (2003)
13. Bundesamt für Sicherheit in der Informationstechnik (BSI): Fingerprint spoof detection protection profile FSDPP v1.8. Common Criteria Portal (2008)
14. Cappelli, R.: Synthetic fingerprint generation. In: Handbook of Fingerprint Recognition, pp. 270–302. Springer (2009)
15. Cappelli, R., Maio, D., Lumini, A., Maltoni, D.: Fingerprint image reconstruction from standard templates. *IEEE Trans. on Pattern Analysis and Machine Intelligence* **29**, 1489–1503 (2007)
16. Cappelli, R., Maio, D., Maltoni, D.: Modelling plastic distortion in fingerprint images. In: Proc. Int. Conf. on Advances in Pattern Recognition (ICAPR), pp. 369–376. Springer LNCS-2013 (2001)
17. Casula, R., Micheletto, M., Orr, G., Delussu, R., Concas, S., Panzino, A., Marcialis, G.: Livdet 2021 fingerprint liveness detection competition into the unknown. In: Proc. Int. Joint Conf. on Biometrics (IJCB 2021) (2021). DOI 10.1109/IJCB52358.2021.9484399
18. Centro Criptologico Nacional (CCN): Characterizing attacks to fingerprint verification mechanisms CAFVM v3.0. Common Criteria Portal (2011)
19. CESG: Communications-Electronics Security Group - Biometric Working Group (BWG) (2001). <https://www.cesg.gov.uk/policyguidance/biometrics/Pages/index.aspx>
20. Chang, S., Larin, K.V., Mao, Y., Almuhtadi, W., Flueraru, C.: Fingerprint spoof detection using near infrared optical analysis. In: J. Wang (ed.) State of the Art in Biometrics, pp. 57–84. Intechopen (2011)
21. Chen, Y., Dass, S., Ross, A., Jain, A.K.: Fingerprint deformation models using minutiae locations and orientations. In: Proc. IEEE Workshop on Applications of Computer Vision (WACV), pp. 150–156 (2005)

22. Chen, Y., Jain, A.K.: Fingerprint deformation for spoof detection. In: Proc. IEEE Biometric Symposium (BSym), pp. 19–21 (2005)
23. Cheng, Y., Larin, K.V.: Artificial fingerprint recognition using optical coherence tomography with autocorrelation analysis. *Applied Optics* **45**, 9238–9245 (2006)
24. Cheng, Y., Larin, K.V.: In vivo two- and three-dimensional imaging of artificial and real fingerprints with optical coherence tomography. *IEEE Photonics Technology Letters* **19**, 1634–1636 (2007)
25. Choi, H., Kang, R., Choi, K., Jin, A.T.B., Kim, J.: Fake-fingerprint detection using multiple static features. *Optical Engineering* **48**, 047,202 (2009)
26. Chugh, T., Cao, K., Jain, A.K.: Fingerprint spoof buster: Use of minutiae-centered patches. *IEEE Transactions on Information Forensics and Security* **13**, 2190–2202 (2018). DOI 10.1109/TIFS.2018.2812193
27. Chugh, T., Jain, A.K.: Fingerprint spoof detector generalization. *IEEE Transactions on Information Forensics and Security* **16**, 42–55 (2021). DOI 10.1109/TIFS.2020.2990789
28. Coli, P.: Vitality detection in personal authentication systems using fingerprints. Ph.D. thesis, Università di Cagliari (2008)
29. Coli, P., Marcialis, G.L., Roli, F.: Power spectrum-based fingerprint vitality detection. In: Proc. IEEE Workshop on Automatic Identification Advanced Technologies (AutoID), pp. 169–173 (2007)
30. Coli, P., Marcialis, G.L., Roli, F.: Vitality detection from fingerprint images: A critical survey. In: Proc. Int. Conf. on Biometrics (ICB), LNCS 4642, pp. 722–731. Springer (2007)
31. Coli, P., Marcialis, G.L., Roli, F.: Fingerprint silicon replicas: static and dynamic features for vitality detection using an optical capture device. *Int. Journal of Image and Graphics* pp. 495–512 (2008)
32. DeCann, B., Tan, B., Schuckers, S.: A novel region based liveness detection approach for fingerprint scanners. In: Proc. IAPR/IEEE Int. Conf. on Biometrics, pp. 627–636. Springer LNCS-5558 (2009)
33. Derakhshani, R., Schuckers, S., Hornak, L., O’Gorman, L.: Determination of vitality from non-invasive biomedical measurement for use in fingerprint scanners. *Pattern Recognition* **36**, 383–396 (2003)
34. Diaz-Santana, E., Parziale, G.: Liveness detection method (2008). EP1872719
35. Franco, A., Maltoni, D.: Fingerprint synthesis and spoof detection. In: N.K. Ratha, V. Govindaraju (eds.) *Advances in Biometrics: Sensors, Algorithms and Systems*, pp. 385–406. Springer (2008)
36. Galbally, J., Alonso-Fernandez, F., Fierrez, J., Ortega-Garcia, J.: A high performance fingerprint liveness detection method based on quality related features. *Future Generation Computer Systems* **28**, 311–321 (2012)
37. Galbally, J., Cappelli, R., Lumini, A., de Rivera, G.G., Maltoni, D., Fierrez, J., Ortega-Garcia, J., Maio, D.: An evaluation of direct and indirect attacks using fake fingers generated from ISO templates. *Pattern Recognition Letters* **31**, 725–732 (2010)
38. Galbally, J., Fierrez, J., Alonso-Fernandez, F., Martinez-Diaz, M.: Evaluation of direct attacks to fingerprint verification systems. *Journal of Telecommunication Systems, Special Issue of Biometrics Systems and Applications* **47**, 243–254 (2011)
39. Galbally, J., Marcel, S., Fierrez, J.: Image quality assessment for fake biometric detection: Application to iris, fingerprint and face recognition. *IEEE Trans. on Image Processing* **23**(2), 710–724 (2014). DOI <http://dx.doi.org/10.1109/TIP.2013.2292332>
40. Ghiani, L., Yambay, D.A., V. Mura and, G.L.M., Roli, F., Schuckers, S.C.: Review of the fingerprint liveness detection (livdet) competition series: 2009 to 2015. *Image and Vision Computing* **58**, 110–128 (2017). DOI 10.1016/j.imavis.2016.07.002
41. Hadid, A., Evans, N., Marcel, S., Fierrez, J.: Biometrics systems under spoofing attack: an evaluation methodology and lessons learned. *IEEE Signal Processing Magazine* **32**(5), 20–30 (2015). DOI <https://doi.org/10.1109/MSP.2015.2437652>
42. Hariri, M., Shokouhi, S.B.: Possibility of spoof attack against robustness of multibiometric authentication systems. *SPIE Journal on Optical Engineering* **50**, 079,001 (2011)

43. Jain, A.K., Deb, D., Engelsma, J.J.: Biometrics: Trust, but verify (2021)
44. Jia, J., Cai, L.: Fake finger detection based on time-series fingerprint image analysis. In: Proc. IEEE Int. Conf. on Intelligent Computing (ICIC), pp. 1140–1150. Springer LNCS-4681 (2007)
45. Jin, C., h. Kim, s. Elliott: Liveness detection of fingerprint based on band-selective Fourier spectrum. In: Proc. Int. Conf. on Information Security and Cryptology (ICISC), pp. 168–179. Springer LNCS-4817 (2007)
46. Jin, S., Bae, Y., Maeng, H., Lee, H.: Fake fingerprint detection based on image analysis. In: Proc. SPIE 7536, Sensors, Cameras, and Systems for Industrial/Scientific Applications XI, p. 75360C (2010)
47. Kallo, I., Kiss, A., Podmaniczky, J.T.: Detector for recognizing the living character of a finger in a fingerprint recognizing apparatus (2001). 6,175,64
48. Kang, H., Lee, B., Kim, H., Shin, D., Kim, J.: A study on performance evaluation of the liveness detection for various fingerprint sensor modules. In: Proc. Int. Conf. on Knowledge-Based Intelligent Information and Engineering Systems (KES), pp. 1245–1253. Springer LNAI-2774 (2003)
49. Karampidis, K., Rousouliotis, M., Linardos, E., Kavallieratou, E.: A comprehensive survey of fingerprint presentation attack detection. *J. Surveill. Secur. Saf.* **2**, 117–61 (2021)
50. Kim, J., Choi, H., Lee, W.: Spoof detection method for touchless fingerprint acquisition apparatus (2011). 1054314
51. Lane, M., Lordan, L.: Practical techniques for defeating biometric devices. Master's thesis, Dublin City University (2005)
52. Lapsley, P., Less, J., Pare, D., Hoffman, N.: Anti-fraud biometric sensor that accurately detects blood flow (1998). 5,737,439
53. Larin, K.V., Cheng, Y.: Three-dimensional imaging of artificial fingerprint by optical coherence tomography. In: Proc. SPIE Biometric Technology for Human Identification (BTHI), vol. 6944, p. 69440M (2008)
54. Lee, H., Maeng, H., Bae, Y.: Fake finger detection using the fractional Fourier transform. In: Proc. Biometric ID Management and Multimodal Communication (BioID), LNCS 5707, pp. 318–324. Springer (2009)
55. Li, S.Z. (ed.): Encyclopedia of Biometrics. Springer (2009)
56. Maltoni, D., Maio, D., Jain, A., Prabhakar, S.: Handbook of Fingerprint Recognition. Springer (2009)
57. Manapuram, R.K., Ghosn, M., Larin, K.V.: Identification of artificial fingerprints using optical coherence tomography technique. *Asian Journal of Physics* **15**, 15–27 (2006)
58. Marasco, E., Ding, Y., Ross, A.: Combining match scores with liveness values in a fingerprint verification system. In: Proc. IEEE Int. Conf. on Biometrics: Theory, Applications and Systems (BTAS), pp. 418–425 (2012)
59. Marasco, E., Ross, A.: A survey on antispoofing schemes for fingerprint recognition systems. *ACM Comput. Surv.* **47**(2) (2014). DOI 10.1145/2617756. URL <https://doi.org/10.1145/2617756>
60. Marasco, E., Sansone, C.: An anti-spoofing technique using multiple textural features in fingerprint scanners. In: Proc. IEEE Workshop on Biometric Measurements and Systems for Security and Medical Applications (BIOMS), pp. 8–14 (2010)
61. Marasco, E., Sansone, C.: Combining perspiration- and morphology-based static features for fingerprint liveness detection. *Pattern Recognition Letters* **33**, 1148–1156 (2012)
62. Marcialis, G.L., Coli, P., Roli, F.: Fingerprint liveness detection based on fake finger characteristics. *Int. Journal of Digital Crime and Forensics* **4**, 1–19 (2012)
63. Marcialis, G.L., Lewicke, A., Tan, B., Coli, P., Grimberg, D., Congiu, A., Tidu, A., Roli, F., Schuckers, S.: First international fingerprint liveness detection competition – livdet 2009. In: Proc. IAPR Int. Conf. on Image Analysis and Processing (ICIAP), pp. 12–23. LNCS-5716 (2009)
64. Marcialis, G.L., Roli, F., Tidu, A.: Analysis of fingerprint pores for vitality detection. In: Proc. IEEE Int. Conf. on Pattern Recognition (ICPR), pp. 1289–1292 (2010)

65. Martinsen, O.G., Clausen, S., Nysather, J.B., Grimmes, S.: Utilizing characteristic electrical properties of the epidermal skin layers to detect fake fingers in biometric fingerprint systems—a pilot study. *IEEE Trans. on Biomedical Engineering* **54**, 891–894 (2007)
66. Matsumoto, T., Matsumoto, H., Yamada, K., Hoshino, S.: Impact of artificial gummy fingers on fingerprint systems. In: *Proc. SPIE Optical Security and Counterfeit Deterrence Techniques IV*, vol. 4677, pp. 275–289 (2002)
67. Memon, S., Manivannan, N., Balachandran, W.: Active pore detection for liveness in fingerprint identification system. In: *Proc. IEEE Telecommunications Forum (TelFor)*, pp. 619–622 (2011)
68. Micheletto, M., Marcialis, G.L., Orr, G., Roli, F.: Fingerprint recognition with embedded presentation attacks detection: Are we ready? *IEEE Transactions on Information Forensics and Security* **16**, 5338–5351 (2021). DOI 10.1109/TIFS.2021.3121201
69. Moon, Y.S., Chen, J.S., Chan, K.C., So, K., Woo, K.C.: Wavelet based fingerprint liveness detection. *Electronic Letters* **41** (2005)
70. Nasiri-Avanaki, M.R., Meadway, A., Bradu, A., Khoshki, R.M., Hojjatoleslami, A., Podoleanu, A.G.: Anti-spoof reliable biometry of fingerprints using en-face optical coherence tomography. *Optics and Photonics Journal* **1**, 91–96 (2011)
71. NexIDBiometrics: (2012). <http://nexidbiometrics.com/>
72. Nikam, S., Argawal, S.: Curvelet-based fingerprint anti-spoofing. *Signal, Image and Video Processing* **4**, 75–87 (2010)
73. Nikam, S.B., Agarwal, S.: Feature fusion using Gabor filters and cooccurrence probabilities for fingerprint antispoofing. *Int. Journal of Intelligent Systems Technologies and Applications* **7**, 296–315 (2009)
74. Nikam, S.B., Argawal, S.: Ridgelet-based fake fingerprint detection. *Neurocomputing* **72**, 2491–2506 (2009)
75. Nixon, K.A., Aimale, V., Rowe, R.K.: Spoof detection schemes. In: A.K. Jain, P. Flynn, A. Ross (eds.) *Handbook of Biometrics*, pp. 403–423. Springer (2008)
76. Nixon, K.A., Rowe, R.K.: Multispectral fingerprint imaging for spoof detection. In: *Proc. SPIE 5779, Biometric Technology for Human Identification II (BTHI)*, pp. 214–225 (2005)
77. NPL: National Physical Laboratory: Biometrics (2010). <http://www.npl.co.uk/biometrics>
78. Optel: (2012). <http://www.optel.pl/>
79. Orr, G., Tuveri, P., Casula, R., Bazzoni, C., Dessalvi, G., Micheletto, M., Ghiani, L., Marcialis, G.: Livdet 2019 fingerprint liveness detection competition in action 2019. In: *Proc. IEEE/IAPR Int. Conf. on Biometrics (ICB 2019)* (2019). DOI 10.1109/ICB45273.2019.8987281
80. Park, E., Cui, X., Nguyen, T.H.B., Kim, H.: Presentation attack detection using a tiny fully convolutional network. *IEEE Transactions on Information Forensics and Security* **14**, 3016–3025 (2019). DOI 10.1109/TIFS.2019.2907184
81. Parthasaradhi, S., Derakhshani, R., Hornak, L., Schuckers, S.: Time-series detection of perspiration as a liveness test in fingerprint devices. *IEEE Trans. on Systems, Man and Cybernetics - Part C: Applications and Reviews* **35**, 335–343 (2005)
82. PosID: (2012). <http://www.posid.co.uk/>
83. van der Putte, T., Keuning, J.: Biometrical fingerprint recognition: don't get your fingers burned. In: *Proc. IFIP Conference on Smart Card Research and Advanced Applications*, pp. 289–303 (2000)
84. Rattani, A., Poh, N., Ross, A.: Analysis of user-specific score characteristics for spoof biometric attacks. In: *Proc. of IEEE Computer Society Workshop on Biometrics at the Int. Conf. on Computer Vision and Pattern Recognition (CVPR)*, pp. 124–129 (2012)
85. Reddy, P.V., Kumar, A., Rahman, S.M., Mundra, T.S.: A new antispoofing approach for biometric devices. *IEEE Trans. on Biomedical Circuits and Systems* **2**, 328–337 (2008)
86. Rowe, R.K., Nixon, K.A., Butler, P.W.: Multispectral fingerprint image acquisition. In: N. Ratha, V. Govindaraju (eds.) *Advances in biometrics: Sensors, algorithms and systems*, pp. 3–23. Springer (2008)
87. Sandstrom, M.: Liveness detection in fingerprint recognition systems. Master's thesis, Linköping University (2004)

88. Schuckers, S., Abhyankar, A.: A wavelet based approach to detecting liveness in fingerprint scanners. In: Proc. Biometric Authentication Workshop (BioAW), pp. 278–386. Springer LNCS-5404 (2004)
89. Sengottuvelan, P., Wahi, A.: Analysis of living and dead finger impressions identification for biometric applications. In: Proc. Int. Conf. on computational Intelligence and Multimedia Applications (2007)
90. Setlak, D.R.: Fingerprint sensor having spoof reduction features and related methods (1999). 5,953,441
91. Singh, J.M., Madhun, A., Li, G., Ramachandra, R.: A survey on unknown presentation attack detection for fingerprint. In: S. Yildirim Yayilgan, I.S. Bajwa, F. Sanfilippo (eds.) Intelligent Technologies and Applications, pp. 189–202. Springer International Publishing, Cham (2021)
92. Sousedik, C., Busch, C.: Presentation attack detection methods for fingerprint recognition systems: a survey. *IET Biometrics* **3**, 219–233(14) (2014). URL <http://digital-library.theiet.org/content/journals/10.1049/iet-bmt.2013.0020>
93. Sousedik, C., Busch, C.: Presentation attack detection methods for fingerprint recognition systems: a survey. *IET Biom.* **3**(4), 219–233 (2014). DOI 10.1049/iet-bmt.2013.0020. URL <https://doi.org/10.1049/iet-bmt.2013.0020>
94. Spinoulas, L., Mirzaalian, H., Hussein, M.E., AbdAlmageed, W.: Multi-modal fingerprint presentation attack detection: Evaluation on a new dataset. *IEEE Transactions on Biometrics, Behavior, and Identity Science* **3**, 347–364 (2021). DOI 10.1109/TBIOM.2021.3072325
95. Sten, A., Kaseva, A., Virtanen, T.: Fooling fingerprint scanners - biometric vulnerabilities of the precise biometrics 100 SC scanner. In: Proc. Australian Information Warfare and IT Security Conference (2003)
96. Tabula Rasa: Trusted biometrics under spoofing attacks (tabula rasa) (2010). (<http://www.tabularasa-euproject.org/>)
97. Tan, B., Schuckers, S.: Comparison of ridge- and intensity-based perspiration liveness detection methods in fingerprint scanners. In: Proc. SPIE Biometric Technology for Human Identification III (BTHI III), vol. 6202, p. 62020A (2006)
98. Tan, B., Schuckers, S.: A new approach for liveness detection in fingerprint scanners based on valley noise analysis. *Journal of Electronic Imaging* **17**, 011,009 (2008)
99. Thalheim, L., Krissler, J.: Body check: biometric access protection devices and their programs put to the test. *ct magazine* pp. 114–121 (2002)
100. Uchida, K.: Image-based approach to fingerprint acceptability assessment. In: Proc. Int. Conf. on Biometric Authentication, LNCS 3072, pp. 194–300. Springer (2004)
101. Ultra-Scan: (2012). <http://www.ultra-scan.com/>
102. VirdiTech: (2012). <http://www.virditech.com/>
103. Wang, L., El-Maksoud, R.A., Sasian, J.M., William, Kuhn, P., Gee, K., 2009, V.S.V.: A novel contactless aliveness-testing fingerprint sensor. In: Proc. SPIE Novel Optical Systems Design and Optimization XII, vol. 7429, p. 742915 (2009)
104. de Water, M.V.: Can fingerprints be forged? *The Science News-Letter* **29**, 90–92 (1936)
105. Wehde, A., Beffel, J.N.: Fingerprints can be forged. Tremonia Publish Co. (1924)
106. Wiehe, A., Sondrol, T., Olsen, K., Skarderud, F.: Attacking fingerprint sensors. Tech. rep., NISlab, Gjovik University College (2004)
107. Willis, D., Lee, M.: Biometrics under our thumb. *Network Computing* (1998). Available on line at <http://www.networkcomputing.com/>
108. Xia, Z., Yuan, C., Lv, R., Sun, X., Xiong, N.N., Shi, Y.: A novel weber local binary descriptor for fingerprint liveness detection. *IEEE Transactions on Systems, Man, and Cybernetics: Systems* **50**, 1526–1536 (2020). DOI 10.1109/TSMC.2018.2874281
109. Yambay, D., Ghiani, L., Denti, P., Marcialis, G.L., Roli, F., Schuckers, S.: LivDet 2011 - fingerprint liveness detection competition 2011. In: Proc. Int. Joint Conf. on Biometrics (IJCB) (2011)

110. Yau, W.Y., Tran, H.L., Teoh, E.K.: Fake finger detection using an electrotactile display system. In: Proc. Int. Conf. on Control, Automation, Robotics and Vision (ICARCV), pp. 17–20 (2008)
111. Yau, W.Y., Tran, H.T., Teoh, E.K., Wang, J.G.: Fake finger detection by finger color change analysis. In: Proc. Int. Conf. on Biometrics (ICB), LNCS 4642, pp. 888–896. Springer (2007)
112. Yoon, S., Feng, J., Jain, A.K.: Altered fingerprints: analysis and detection. *IEEE Trans. on Pattern Analysis and Machine Intelligence* **34**, 451–464 (2012)
113. Zhang, Y., Tian, J., Chen, X., Yang, X., Shi, P.: Fake finger detection based on thin-plate spline distortion model. In: Proc. IAPR Int. Conf. on Biometrics, pp. 742–749. Springer LNCS-4642 (2007)